

by Schneider Electric

Industrial PC PS5000 SERIES

Powerful Solution





Real Performance

Slim


Drastically slimmer profile with less wasted space. An ultra-thin design only 40% as deep as conventional products.

High Performance

The latest technology gives this IPC excellent performance: Upgraded 280% compared to PS4000.

Smart

Multi-touch display enables operation similar to a tablet or smartphone.



PS-5811W



April 2016

www.proface.com/PS50007

PS5000 Series

Full lineup to meet all your specific needs. Find your ideal combination and model on the Web. >>> http://www.proface.com/ps5000bto/



Danal Type	CPU/ Memory	Rated Voltage/	OS	Storage Media	Projected Capacitive				Resistive Film	
Panel Type		Slot			22″w	19″w	15″w	10″w	15″	
Modular Type Replace only the Display unit for easy maintenance.	Core i7 model/ 8GB or 16GB	24VDC/ 100-240VAC	Windows7 Ultimate (64bit) MUI	HDD Unit	~	~	V		V	
	Celeron model/ 4GB or 8GB	0/2 slots	or Windows Embedded 8.1 Industry (64bit) MUI	(500GB,1TB) SSD (80GB,160GB, 240GB	~	V	V		V	
Slim Type Integrated type saves space.	Core i3 model/ 8GB	24VDC/ 100-240VAC	or Windows Embedded Standard 7 Premium (64bit) MUI	CFast Card (16GB) *WES7 only		V Enclosed model available.	V			
	Atom model/ 4GB	0 slot					X	~		
Box Type	CPU/	Rated Voltage/	0	Storage / Ae. Via				ion Slot		
Book mount style.	Memory Core i7 model/	Slot	Wind Ultimate (6	H			Oslot	2slot		
	8GB or 16GB	24VDC/ 100-240VAC	o Windows En	(500Gb,1TB) SSD (LOGF,160GB,240GB) CFast Card (16GB) *WES7 only			V	~		
	Celeron model/ 4GB or 8GB	0/2 slots	Industry(6 c Windows E Standard 7 Prer				\checkmark	~		
A Variety of Interfaces Choose interface options for more functions such as Serial, Gigabit Ethernet, DIO and more. Bebugging can be done on a table. Bebugging can be done on a table.										
Pro-face Rem te HMI Remote Monitoring Software for mobile Pro-face Rem te										
Fan-less Design No need for regular maintenance, and peace-of-mind dispite of dust and noise at the manufacturing site.						Flexible installation Product can be installed with VESA mounting arm, and an enclosed model with IP66 is also available.				









A WARNING

HAZARD OF OPERATOR INJURY, OR UNINTENDED EQUIPMENT DAMAGE Before operating any of these products, be sure to read all related manuals thoroughly. Failure to follow these instructions can result in death, serious injury or equipment damage.

For printing purposes, the colors in this catalog may differ from those of the actual unit.
Actual user screens may differ from the screens shown here.
All product names used in this catalog are the registered trademarks or trademarks of their respective companies.
All information contained in this catalog is subject to change without notice.
All information contained in this catalog is subject to change without notice.

